

Chubb safes 2" Strongroom Doors are specially designed and constructed to resist against high speed drills, force and fire.



2" Strongroom Door

BURGLARY-RESISTANT PROTECTION

Key Features

- **Door** – Solid door slab with a protective thickness of 50mm (2") forms the basis of the door, which has an overall thickness of 165mm. Filled with a specially formulated Chubb safes F80 barrier material reinforced with steel fibers provides resistant to high speed drilling, oxy-acetylene cuttings and jack attacks.
- **Boltwork** – Secured by 7 active front bolts, 2 active top bolts, 2 active bottom bolts and 7 passive back bolts. Each bolt has a diameter of 32 mm.
- **Locking** – Secured with a single 3-wheel Keyless Combination Lock capable of 1,000,000 change codes and a 8-lever double bitted Key Lock as standard. Both Locks operated independently of each other. Key Lock is protected by Manganese Plate.
- **Fire Resistance** – Tested in accordance with BS476 Part 22:1987 FireTest on Building Material and Structures for a 120 minutes fire resistant rating.
- **Relocker** – Keyless Combination Lock is protected by Glass Relocker. Any forced attempt to dislodge the locks would activate these secondary locking devices. This restricts the movement of the internal boltwork system. Relockers are further protected by drill resistant hard plates to serve as extra protection.
- **Frame** – The “wrapped around the wall” door frame is fabricated from steel sections, bent to form a single structure. Vestibule side frames at full height of the door are attached to the frame and grip the inside of the wall. This design provides stronger resistance against attacks to the door.
- **Finish** – The door comes standard with a painted grey primer based finish.



Chubb safes
Trusted the world over.

VAULTS &
VAULT DOORS

Product Specifications

Model	External Dimensions (mm)	Clear Opening (mm)	Wall Opening (mm)	Wall Thickness (mm)	Approx. Nett Weight (Kg)
2"	2110 (H) x 1273 (w)	1920 (H) x 814 (w)	2060 (H) x 1070 (w)	200 mm (inclusive of Plastering)	640 kg (Door) and 20 kg (Gate)

Secured by a 8-lever double bitted key lock from Germany



Heavy cylindrical moving bolts



Secured by a High Security 3-wheel Keyless Combination Lock capable of 1,000,000 changes of code. The operation of this lock is simple. The code can be changed easily and security can be maintained over the safe whenever there is a change of staff.

Options

Day Gate – An Optional Day Gate can be fitted to the door for ventilation during the day or as control when the door is open. The Day gate is secured by two high security 5-lever Mortice Deadlocks.

Locking Option:



Electronic lock

When ordering, please state:

- Wall Thickness
- Type of wall e.g. brick, R.C. etc.
- Hung of door required.
- If to be installed in multi-story building, state floor/level.
- Path of access to where door is to be installed.

Note:

Chubb Safes Doors are designed primarily against physical attack, but for recommended storage of paper documents and computer media, ask for details of Chubb Safes Fire Resistant Protection Cabinet or Chubb Safes Data Cabinets.

- A Dial Check Lock can be fitted as an option to the combination lock.
- Two or three movement Time Lock may be fitted as an additional requirement.
- Emergency Ventilator can be fitted as an option.



Emergency ventilator



Authorised dealer:

Chubb Safes

Trusted the world over.

GUNNEBO MALAYSIA SDN. BHD. (877658-K)

Suite 13A.01, Level 13A,

Menara Summit,

Persiaran Kewajipan, USJ 1,

47600 Subang Jaya, Selangor

Tel : +603-8024 3050

Fax : +603-8024 3051

Website: www.gunnebo.com.my

E-mail: info.my@gunnebo.com