

Chubb safes 3½" Strongroom Doors are specially designed to meet the demands for a high security installation. Constructed to resist against modern cutting tools such as high speed drills, force and fire.



# 3½" Strongroom Door

BURGLARY - RESISTANT PROTECTION

## Key Features

- **Door** – Solid door slab with a protective thickness of 89mm (3½") forms the basis of the door which has an overall thickness of 226mm. Filled with a specially formulated F80 barrier material reinforced with steel fibers provides resistant to high speed drilling, oxy-acetylene cuttings and jack attacks.
- **Boltwork** – Secured by 7 active front bolts, 2 active top bolts, 2 active bottom bolts and 7 fixed rear bolts. Each bolt has a diameter of 50mm.
- **Locking** – Secured with a single 3-wheel Keyless Combination Lock capable of 1,000,000 change codes and a 11-lever double bitted Key Lock as standard. Both Locks operated independently of each other.
- **Relocker** – Protected by two Glass Relocker. Any forced attempts to dislodge the locks would activate both relockers. This restricts the movement of the internal boltwork system. Relockers are further protected by Chubb safes patented Torch and Drill Resistant (TDR) material.
- **Frame** – The "wrapped around the wall" door frame is fabricated from steel sections, bent to form a single structure. Vestibule side frames at full height of the door are attached to the frame and grip the inside of the wall. This design provides stronger resistance against attacks to the door.
- **Emergency Ventilator** – An emergency ventilator is integrated into the door frame to provide fresh air, allow two way conversation and to supply food or water to anyone trapped in the strongroom.
- **Lighting Control** – A relay micro switch is fitted to the door to control the electric lighting in the room and to ensure that when the door is closed, all lighting within the room is switched off.
- **Alarm Micro Switch** – A relay micro switch is fitted to the door for possible connection to the main intruder alarm system as an additional protection.



**Chubb safes**  
Trusted the world over.

VAULTS &  
VAULT DOORS

## Product Specifications

Model	External Dimensions (mm)	Clear Opening (mm)	Wall Opening (mm)	Wall Thickness (mm)	Approx. Nett Weight (Kg)
3½"	2110 (H) x 1312 (W)	1920 (H) x 814 (W)	2080 (H) x 1150 (W)	300mm (Inclusive of Plastering)	Door : 740 kg Day Gate: 20 kg



Emergency ventilator



Heavy cylindrical moving bolts



Secured by a High Security 3-wheel Keyless Combination Lock certificated under **UL Group 2, VdS Class 1, Cen A.**



Secured by a 11 lever double bitted high security Key Lock from Germany with non detachable key bit

## Options

- **Day Gate** – An Optional Day Gate can be fitted to the door for ventilation during the day or as control when the door is open. The Day Gate is secured by two high security 5-lever Mortice Deadlocks.
- **Finish** – The door comes standard with a painted grey primer based finish with an option for a stainless steel clad finish.
- **Locks** – A Dial Check Lock can be fitted as an option to the combination lock. Two or three movement Timelocks or electronic combination lock are also available. A 4-wheel Keyless Combination Lock can be fitted to replace the 3-wheel Keyless Combination Lock as an option.

### When ordering, please state :

- Wall thickness.
- Type of wall e.g. brick, R.C. etc.
- Hung of door required.
- If to be installed in multi-storey building, state floor level.
- Path of access to where door is to be installed.

### Note :

Chubb safes Doors are designed primarily against physical attack, but for recommended storage of paper documents and computer media, ask for details of Chubb safes Fire Resistant Protection Cabinet or Chubb safes Data Cabinets.

Authorised dealer:



# Chubb safes

*Trusted the world over.*

**GUNNEBO MALAYSIA SDN. BHD.** (877658-K)  
 Suite 13A.01, Level 13A,  
 Menara Summit,  
 Persiaran Kewajipan, USJ 1,  
 47600 Subang Jaya, Selangor  
 Tel : +603-8024 3050  
 Fax : +603-8024 3051  
 Website: [www.gunnebo.com.my](http://www.gunnebo.com.my)  
 E-mail: [info.my@gunnebo.com](mailto:info.my@gunnebo.com)